


日期/Date
档案员
Filing Clerk



技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 350A
- 接触电阻: $\leq 0.3m\Omega$
- 线径范围: $16mm^2$
- 剥线长度: 26mm
- 冷压模具: 按照 DIN 46 235
- 压力要求: 130kN
- 可插拔次数: ≥ 500

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 350A
- Contact resistance: $\leq 0.3m\Omega$
- Wire gauge: $16mm^2$
- Stripping length: 26mm
- Crimp dies: acc. to DIN 46 235
- Pressing force: 130kN
- Mating cycles: ≥ 500

				表面处理 Finish		-				图号 Drawing No.	-
				材料 Material		-				产品代号 Part Code	CHSM350-16
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date					产品料号 Part No.	1010291101501
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	350A冷压公插针
绘图 Drawn	DN YE	23.12.2020	标准化 Stand.	-	-	1:1	V1.1	54.2g	-		
审核 Checked	HZ LAN	23.12.2020									
工艺 Process	-	-	批准 Approved	HQ ZHANG	23.12.2020			All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD